

Printing date 11.01.2023 Version number 8 Revision: 01.12.2022

1 Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name: ATE Assembly and Preserving Fluid VP 1449/8

Article number: 03.9902-03xx.x / 70000x

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Preservative

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Continental Aftermarket & Services GmbH

Sodener Straße 9

D-65824 Schwalbach am Taunus

Tel: +49-6196-87-0

Further information obtainable from:

Gefahrstoffmanagement Konzern, Zentrales Materiallabor

ate.sicherheit@contiautomotive.com

Emergency telephone number: +49-6132-84463 (24 h) 190 languages spoken

2 Hazards identification

Classification of the substance or mixture



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Aquatic Acute 2 H401 Toxic to aquatic life.

Label elements

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms GHS09

Signal word Void

Hazard statements

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P273 Avoid release to the environment.

P391 Collect spillage.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)



Printing date 11.01.2023 Version number 8 Revision: 01.12.2022

Trade name: ATE Assembly and Preserving Fluid VP 1449/8

	(Con	td. of page 1)
Dangerous components:		
5892-47-7	2,4,6-Tri-sec-butylphenol	< 10%
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	
	2,2´-(Octylimino)bisethanol	< 3%
	Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Acute Tox. 5, H313; Aquatic Chronic 3, H412	
85507-95-5	9-Oxadeceonic acid (Z)-compd.with N-coco alkyl-1,1'-iminobis(2-propanol)	< 1%
	Aquatic Acute 1, H400; Skin Irrit. 2, H315; Aquatic Chronic 3, H412	

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

Description of first aid measures

General information: Remove contaminated clothes and shoes immediately.

After inhalation: Supply fresh air and to be sure call for a doctor.

After skin contact:

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Call a doctor immediately.

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

May be released in case of fire: CO, CO2, NOx

Advice for firefighters Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)



Printing date 11.01.2023 Version number 8 Revision: 01.12.2022

Trade name: ATE Assembly and Preserving Fluid VP 1449/8

See Section 13 for disposal information.

(Contd. of page 2)

7 Handling and storage

Handling:

Precautions for safe handling Open and handle receptacle with care.

Information about fire - and explosion protection: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store cool and dry.

Information about storage in one common storage facility:

Store away from flammable substances.

Store away from foodstuffs.

Further information about storage conditions:

This product is hygroscopic.

Store in dry conditions.

Storage class according to TRGS 510: 10 combustible liquids.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Use skin protection cream for skin protection.

Respiratory protection: Not necessary if room is well-ventilated.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7 mm

NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses

Limitation and supervision of exposure into the environment

See section 6 and 7. No additional measures necessary.

IN



Printing date 11.01.2023 Version number 8 Revision: 01.12.2022

Trade name: ATE Assembly and Preserving Fluid VP 1449/8

(Contd. of page 3)

Physical and chemical properti	es		
Information on basic physical and chemical properties General Information			
Appearance: Form:	Fluid		
Colour:	Yellow		
Odour:	Weak, characteristic		
Odour threshold:	Not determined.		
pH-value at 20 °C:	8-9 (FMVSS 116)		
Change in condition Melting point/freezing point: Initial boiling point and boiling ra	<-30 °C (DIN 51583) ange: >300 °C (FMVSS 116)		
Flash point:	>145 °C (DIN EN 22719 - closed cup)		
Flammability (solid, gas):	Not applicable.		
Ignition temperature:	>300 °C (DIN 51794)		
Decomposition temperature:	345 °C		
Auto-ignition temperature:	Product is not selfigniting.		
Explosive properties:	Product does not present an explosion hazard.		
Explosion limits:			
Lower:	Not determined.		
Upper:	Not determined.		
Vapour pressure at 20 °C:	0.1 hPa		
Density at 20 °C:	1 g/cm³ (DIN 51757)		
Relative density	Not determined.		
Vapour density	Not determined.		

Not determined. Insoluble.

Not determined.

Not determined.

600-800 mm²/s

No further relevant information available.

10 Stability and reactivity

Kinematic at 20 °C:

Other information

Reactivity No further relevant information available.

Chemical stability

Evaporation rate

Viscosity: Dynamic:

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

Partition coefficient: n-octanol/water:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)



Printing date 11.01.2023 Version number 8 Revision: 01.12.2022

Trade name: ATE Assembly and Preserving Fluid VP 1449/8

(Contd. of page 4)

11 Toxicological information

Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:

The ATE values (all routes of exposure) exceeding the upper limits of classification to Category 5

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
5892-47	7-7 2,4,	6-Tri-sec-butylphenol	
Oral	LD50	>2,000 mg/kg (rat)	
15520-0	05-5 2,2	2´-(Octylimino)bisethanol	
Oral	LD50	1,157 mg/kg (rat) (OECD 401)	
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)	

Primary irritant effect:

Skin corrosion/irritation Slight irritant effect - does not require labelling.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) None.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

Toxicity

Aquatic toxicity:		
LC50	>100 mg/L (fish) (OECD 203 96 h)	
5892-47-7 2,4,6-Tri-sec-butylphenol		
EC50	0.675 mg/l (daphnia) (OECD 202 48 h)	
LC50 (static)	static) 2.2-5 mg/L (fish) (OECD 203 96 h)	
NOEC	0.0675 mg/L (Algae)	
ErC50 (static)	0.391 mg/L (Algae) (OECD 201 72 h)	
ErC10 (static)	0.258 mg/L (Algae) (OECD 201 72 h)	
15520-05-5 2,	15520-05-5 2,2´-(Octylimino)bisethanol	
EC50 (static)	1.35 mg/l (Algae) (OECD 201 72 h)	
	>100 mg/l (bacteria) (OECD 209)	
	19.1 mg/l (daphnia) (OECD 202 48 h)	
LC50	22 mg/L (fish) (OECD 203 96 h)	
ErC10 (static)	0.402 mg/L (Algae) (OECD 201 72 h)	
Davalatawaa a	and dogradahility	

Persistence and degradability

This product is, corresponding to the desired stability, heavily biodegradable.

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 6)



Printing date 11.01.2023 Version number 8 Revision: 01.12.2022

Trade name: ATE Assembly and Preserving Fluid VP 1449/8

(Contd. of page 5)

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14 Transport information

UN-Number ADR, IMDG, IATA	UN3082
UN proper shipping name	
ADR	3082 ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (2,4,6-Tri-sec-
	butylphenol)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (2,4,6-Tri-sec-butylphenol), MARINE
	POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (containing 2,4,6-Tri-sec-butylphenol)

Transport hazard class(es)

ADR, IMDG, IATA



Class Label	9 Miscellaneous dangerous substances and articles.9
Packing group ADR, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances: 2,4,6-Tri-sec-butylphenol
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Danger code:	90
EMS Number:	F-A,S-F
Stowage Category	A
	(0 ()

(Contd. on page 7)



Printing date 11.01.2023 Version number 8 Revision: 01.12.2022

Trade name: ATE Assembly and Preserving Fluid VP 1449/8

	(Contd. of pag
Transport in bulk according to Annex	II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
Transport category	3
Tunnel restriction code	(-)
Remarks:	Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 110607: (USA domestic) 1 800 535 5053
	or international (001) 352 323 3500 Special Provision 375
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 m
Remarks:	Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 110607: (USA domestic) 1 800 535 5053
	or international (001) 352 323 3500
	Special Provision 2.10.2.7
IATA	
Remarks:	Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 110607: (USA domestic) 1 800 535 5053
	or international (001) 352 323 3500 Special Provision A197
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,4,6-TRI-SEC-

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

BUTYLPHENOL), 9, III

No further relevant information available.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 8)



Printing date 11.01.2023 Revision: 01.12.2022 Version number 8

Trade name: ATE Assembly and Preserving Fluid VP 1449/8

(Contd. of page 7)

H412 Harmful to aquatic life with long lasting effects.

Recommended restriction of use For industrial or professional purposes only.

Department issuing SDS:

Gefahrstoffmanagement Konzern ate.sicherheit@contiautomotive.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 5: Acute toxicity – Category 5

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

http://echa.europa.eu/information-on-chemicals/cl-inventory

http://echa.europa.eu/web/guest/information-on-chemicals/registered-substances

http://www.reach-clp-biozid-helpdesk.de/de/Downloads/CLP-VO/CLP_VO_Anhang_VI_Tabelle_3_2.pdf

http://www.safeworkaustralia.gov.au/ * Data compared to the previous version altered.