

Printing date 05.05.2023 Version number 11 Revision: 01.04.2023

1 Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name: Original ATE Brake Fluid SL (DOT 4)

Article number: 03.9901-58xx.x / 7058xx

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture hydraulic liquid

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Continental Aftermarket & Services GmbH

Sodener Straße 9

D-65824 Schwalbach am Taunus

Tel: +49-6196-87-0

Further information obtainable from:

Gefahrstoffmanagement Konzern, Zentrales Materiallabor

ate.sicherheit@contiautomotive.com

Emergency telephone number: +49-6132-84463 (24 h) 190 languages spoken

2 Hazards identification

Classification of the substance or mixture



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Label elements

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms GHS08

Signal word Warning

Hazard-determining components of labelling:

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Hazard statements

H361 Suspected of damaging fertility or the unborn child.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)



Printing date 05.05.2023 Version number 11 Revision: 01.04.2023

Trade name: Original ATE Brake Fluid SL (DOT 4)

		(Contd. of page 1)
Dangerous	components:	
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	≥30-<50%
	Repr. 2, H361	
	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol	≥10-<20%
	Eye Dam. 1, H318; Acute Tox. 5, H313 Specific concentration limits: Eye Dam. 1; H318: C ≥ 30 % Eye Irrit. 2; H319: 20 % ≤ C < 30 %	
111-46-6	2,2'-oxybisethanol	<10%
	Acute Tox. 4, H302	
110-97-4	1,1'-iminodipropan-2-ol	<2%
	Eye Irrit. 2, H319	

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

Description of first aid measures

General information:

Remove contaminated clothes and shoes immediately.

Get medical advice/attention if you feel unwell.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Call a doctor immediately.

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

May be released in case of fire: CO, CO2, NOx

Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions:

Do not allow product to reach sewage system or any water course.

(Contd. on page 3)



Printing date 05.05.2023 Version number 11 Revision: 01.04.2023

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 2)

Do not allow to penetrate the ground/soil.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Storage at room temperature.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from flammable substances.

Further information about storage conditions:

This product is hygroscopic.

Store in dry conditions.

Keep container tightly sealed.

Storage class according to TRGS 510: 10 combustible liquids.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see section 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Use skin protection cream for skin protection.

Respiratory protection:

Respiratory protection required in case of release of vapors / aerosols.

If occupational exposure limits are exceeded, use breathing mask (filter type A). Wear self-contained breathing apparatus in case of danger of oxygen displacement.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7 mm

(Contd. on page 4)



Printing date 05.05.2023 Version number 11 Revision: 01.04.2023

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 3)

NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm
The exact break trough time has to be found out by the manufacturer of the protective gloves and

has to be observed.

Eye protection: Safety glasses

Body protection: Protective work clothing

Limitation and supervision of exposure into the environment

See section 6 and 7. No additional measures necessary.

9 Physical and chemical properties

9 Physical and chemical properties	
Information on basic physical and che General Information Appearance:	mical properties
Form:	Fluid
Colour:	Yellow
Odour: Odour threshold:	Characteristic Not determined.
pH-value at 20 °C:	8.5 (50%) (FMVSS 116)
<u>'</u>	6.5 (50%) (FMV55 110)
Change in condition Melting point/freezing point: Initial boiling point and boiling range	<-70 °C (DIN 51583) s: >260 °C (FMVSS 116)
Flash point:	139 °C (ASTM D 7094 (closed cup))
Flammability (solid, gas):	Not applicable.
Auto-ignition temperature:	>200 °C (DIN 51794)
Decomposition temperature:	ca. 360 °C (DSC)
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits: Lower: Upper:	1.5 Vol % Not determined.
Vapour pressure at 20 °C:	<1 hPa
Density at 20 °C: Relative density Vapour density Evaporation rate water:	1.06 g/cm³ (DIN 51757) Not determined. Not determined. Not determined. Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic at 20 °C:	Not determined. 15-17 mm²/s (FMVSS 116)
Other information	No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

(Contd. on page 5)



Printing date 05.05.2023 Version number 11 Revision: 01.04.2023

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 4)

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

11 Toxicological information

Information on toxicological effects Acute toxicity

, 100.10				
LD/LC5	0 valu	es relevant for classification:		
30989-0	30989-05-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate			
Oral	LD50	>2,000 mg/kg (rat) (OECD 401)		
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)		
111-46-	6 2,2'-0	oxybisethanol		
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rabbit)		
110-97-	4 1,1'-i	minodipropan-2-ol		
Oral	LD50	>2,000 mg/kg (rat) (OECD 401)		
Dermal	LD50	8,000 mg/kg (rabbit)		
Reactio	n mas	s of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol		
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>3,000 mg/kg (rabbit)		

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

Toxicity

Aquatic t	toxicity:	
EC50	6.25 mg/l (bacteria)	
	250-350 mg/l (fish) (DIN 38412 96 h)	
30989-05	5-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	
EC50	>100 mg/l (Algae) (72 h)	
	>100 mg/l (daphnia) (48 h)	
LC50	>100 mg/L (fish) (96 h)	
111-46-6	6 2,2'-oxybisethanol	
EC50	>100 mg/l (Algae)	
	>100 mg/l (daphnia) (DIN 38412 T.11)	
LC50	>100 mg/L (fish) (96 h)	
	(Contd. o	n page 6)

(Contd. on page 6)



Printing date 05.05.2023 Version number 11 Revision: 01.04.2023

Trade name: Original ATE Brake Fluid SL (DOT 4)

		(Contd. of page 5)
	110-97-4 1,1'	-iminodipropan-2-ol
EC50 (static) >100 mg/l (Algae) (72 h)		>100 mg/l (Algae) (72 h)
		>100 mg/l (daphnia) (92/69/EWG 48 h)
	LC50 (static)	>100 mg/L (fish) (OECD 203 96 h)
	Reaction ma	ss of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol
Ī	EC50	>100 mg/l (Algae)
	LC50	>100 mg/L (daphnia)
		>100 mg/L (fish) (DIN 38412 96 h)

Persistence and degradability No further relevant information available.

Other information: The product is easily biodegradable.

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

UN-Number		
ADR, IMDG, IATA	Void	
UN proper shipping name		
ADR, IMDG, IATA	Void	
Transport hazard class(es)		
ADR, IMDG, IATA		
Class	Void	
Packing group		
ADR, IMDG, IATA	Void	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	



Printing date 05.05.2023 Version number 11 Revision: 01.04.2023

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 6)

Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

UN "Model Regulation": Void

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H313 May be harmful in contact with skin.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

Recommended restriction of use For industrial or professional purposes only.

Department issuing SDS:

Gefahrstoffmanagement Konzern

ate.sicherheit@contiautomotive.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 5: Acute toxicity - Category 5

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Repr. 2: Reproductive toxicity - Category 2

Sources

http://echa.europa.eu/information-on-chemicals/cl-inventory

http://echa.europa.eu/web/quest/information-on-chemicals/registered-substances

http://www.reach-clp-biozid-helpdesk.de/de/Downloads/CLP-VO/CLP_VO_Anhang_VI_Tabelle_3_2.pdf http://www.safeworkaustralia.gov.au/

* Data compared to the previous version altered.