

Printing date 30.04.2020

Version number 9

Revision: 01.04.2020

1 Identification

Product identifier

Trade name: Original ATE Brake Fluid SL (DOT 4)

Article number: 03.9901-58xx.x / 7058xx Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Application of the substance / the mixture hydraulic liquid

Details of the supplier of the safety data sheet Manufacturer/Supplier: Continental Aftermarket & Services GmbH Sodener Straße 9 D-65824 Schwalbach am Taunus Tel: +49-69-7603-11 Fax: +49-69-761061

Further information obtainable from:
Gefahrstoffmanagement Konzern, Zentrales Materiallabor ate.sicherheit@contiautomotive.com
Emergency telephone number: +49-6132-84463 (24 h) 190 languages spoken

2 Hazards identification

Classification of the substance or mixture



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Label elements

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS). **Hazard pictograms** GHS08

Signal word Warning

Hazard-determining components of labelling:

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Hazard statements

H361 Suspected of damaging fertility or the unborn child.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

(Contd. on page 2)

— SG



Printing date 30.04.2020

Version number 9

Revision: 01.04.2020

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 1)

≥30-<50%

≥10-<20%

3 Composit	3 Composition/information on ingredients		
	Chemical characterisation: Mixtures Description: Mixture of substances listed below with nonhazardous additions.		
Dangerous	components:		
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate		
	Repr. 2, H361		
	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12- tetraoxahexadecan-1-ol		
	Eye Dam. 1, H318 Specific concentration limits: Eye Dam. 1; H318: C ≥ 30 %		
	Eye Irrit. 2; H319: 20 % ≤ C < 30 %		

	,,	
111-46-6	2,2'-oxybisethanol	<10%
	Acute Tox. 4, H302	
110-97-4	1,1'-iminodipropan-2-ol	<2%
	Eye Irrit. 2, H319	
Additional	information: For the wording of the listed hazard phrases refer to section 16.	

4 First-aid measures

Description of first aid measures

General information: Remove contaminated clothes and shoes immediately.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly. After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. **After swallowing:** Call a doctor immediately.

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

May be released in case of fire: CO, CO2, NOx.

Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

(Contd. on page 3)

SG



Printing date 30.04.2020

Safety Data Sheet according SS 586 : Part 3

Version number 9

Revision: 01.04.2020

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 2)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. **Information about fire - and explosion protection:** No special measures required.

Conditions for safe storage, including any incompatibilities Storage: Requirements to be met by storerooms and receptacles: Storage at room temperature.

Information about storage in one common storage facility:

Not required.

Store away from foodstuffs.

Further information about storage conditions:

This product is hygroscopic.

Store in dry conditions.

Keep container tightly sealed.

Storage class according to TRGS 510: 10 combustible liquids.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

Respiratory protection required in case of release of vapors / aerosols.

Use particulate filter with medium retention capacity for solid and liquid particles (eg EN 143 or 149, type P2 or FFP2).

(Contd. on page 4)

SG



*

Printing date 30.04.2020

Safety Data Sheet according SS 586 : Part 3

Version number 9

Revision: 01.04.2020

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 3)	
Protection of hands:	
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation	
Material of gloves	
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.	
Penetration time of glove material	
Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7 mm	
NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.	
Eye protection: Safety glasses	
Body protection: Protective work clothing	
Limitation and supervision of exposure into the environment	
See section 6 and 7. No additional measures necessary.	
Risk management measures	
Use at industrial site in closed process with occasional controlled exposure or processes with equivalent containment conditions:	
1 to 3 air changes per hour (90 % effectiveness) - basic standard of general ventilation maximum 8 h exposure duration per day	
maximum 40 °C process temperature	
Use of functional fluids in small devices:	
5 to 10 air changes per hour (70 % effectiveness) - good standard of controlled ventilation	

maximum 8 h exposure duration per day maximum 40 °C process temperature

Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Fluid
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value at 20 °C:	8.5
Change in condition	
Melting point/freezing point:	<-70 °C
Initial boiling point and boiling ra	nge: >260 °C
Flash point:	>125 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	210 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.



Printing date 30.04.2020

Safety Data Sheet according SS 586 : Part 3

Version number 9

Revision: 01.04.2020

Trade name: Original ATE Brake Fluid SL (DOT 4)

	(Contd. of page 4
Explosion limits:	
Lower:	Not determined.
Upper:	1.5 Vol %
Vapour pressure at 20 °C:	1.3 hPa
Density at 20 °C:	1.065 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	16 mm²/s
Solvent content:	
Organic solvents:	8.0 %
Solids content:	1.5 %
Other information	No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available. Chemical stability Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. Possibility of hazardous reactions No dangerous reactions known. Conditions to avoid No further relevant information available. Incompatible materials: Strong oxidizing agents Hazardous decomposition products: Carbon monoxide and carbon dioxide Nitrogen oxides (NOx)

11 Toxicological information

Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:

30989-05-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Oral LD50 >2,000 mg/kg (rat) (OECD 401)

Dermal LD50 >2,000 mg/kg (rat) (OECD 402)

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >3,000 mg/kg (rabbit)

111-46-6 2,2'-oxybisethanol

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rabbit)

(Contd. on page 6)

SG



Printing date 30.04.2020

Version number 9

Revision: 01.04.2020

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 5)

110-97-	4 1,1'-	iminodipı	ropan-2-ol

LD50 >2,000 mg/kg (rat) (OECD 401) Oral

Dermal LD50 8,000 mg/kg (rabbit)

Primary irritant effect:

Skin corrosion/irritation No irritant effect.

Serious eye damage/irritation No irritating effect.

Respiratory or skin sensitisation No sensitising effects known.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Repr. 2

Reproductive toxicity

Some evidence of adverse effects on development, based on animal experiments.

12 Ecological information

Toxicity

Aquatic toxic	
EC50	6.25 mg/l (bacteria)
	250-350 mg/l (fish) (DIN 38412 96 h)
	ris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate
EC50	>100 mg/l (Algae) (72 h)
	>100 mg/l (daphnia) (48 h)
LC50	>100 mg/L (fish) (96 h)
	ss of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol
EC50	>100 mg/l (Algae)
LC50	>100 mg/L (daphnia)
	>100 mg/L (fish) (DIN 38412 96 h)
•	-oxybisethanol
EC50	>100 mg/l (Algae)
	>100 mg/l (daphnia) (DIN 38412 T.11)
LC50	>100 mg/L (fish) (96 h)
	-iminodipropan-2-ol
EC50 (static)	>100 mg/l (Algae) (72 h)
	>100 mg/l (daphnia) (92/69/EWG 48 h)
()	>100 mg/L (fish) (OECD 203 96 h)
	and degradability No further relevant information available.
	nation: The product is easily biodegradable. In environmental systems:
	ative potential No further relevant information available.
	oil No further relevant information available.
Additional ed	cological information:
General note	
	I class 1 (German Regulation) (Self-assessment): slightly hazardous for water
system.	undiluted product or large quantities of it to reach ground water, water course or sewage
	BT and vPvB assessment
PBT: Not app	
VDVD. Not on	pplicable
vPvB: Not ap	(Contd. on page

Printing date 30.04.2020

Version number 9

Revision: 01.04.2020

Trade name: Original ATE Brake Fluid SL (DOT 4)

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

UN-Number	
ADR, IMDG, IATA	Void
UN proper shipping name	
ADR, IMDG, IATA	Void
Transport hazard class(es)	
ADR, IMDG, IATA	
Class	Void
Packing group	
ADR, IMDG, IATA	Void
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act - Schedule 1

None of the ingredients are listed.

Poisons Act - Schedule 2, Group II

None of the ingredients are listed.

Health Products Act - First Schedule - Psychotropic Substances

None of the ingredients are listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

(Contd. on page 8)

(Contd. of page 6)

SG



Version number 9

Revision: 01.04.2020

Trade name: Original ATE Brake Fluid SL (DOT 4)

(Contd. of page 7)

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Printing date 30.04.2020

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.

Recommended restriction of use For industrial or professional purposes only.

Department issuing SDS:

Gefahrstoffmanagement Konzern ate.sicherheit@contiautomotive.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration. 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral - Category 4 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Repr. 2: Reproductive toxicity - Category 2 Sources http://echa.europa.eu/information-on-chemicals/cl-inventory http://echa.europa.eu/web/quest/information-on-chemicals/registered-substances http://www.reach-clp-biozid-helpdesk.de/de/Downloads/CLP-VO/CLP VO Anhang VI Tabelle 3 2.pdf http://www.safeworkaustralia.gov.au/

* Data compared to the previous version altered.

SG -