

Printing date 05.02.2024 Version number 4 Revision: 01.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

Article number: 03.9901-66xx.x/7066xx

UFI: UV00-70P4-200D-FU7K

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture hydraulic liquid

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Continental Aftermarket & Services GmbH

Sodener Straße 9

D-65824 Schwalbach am Taunus

Tel: +49-6196-87-0

Further information obtainable from:

Gefahrstoffmanagement Konzern, Zentrales Materiallabor

ate.sicherheit@contiautomotive.com

1.4 Emergency telephone number:

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week).

Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Repr. 2 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified according to the CLP regulation.

Hazard pictograms GHS08

Signal word Warning

Hazard-determining components of labelling:

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Hazard statements

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

ΙE



Printing date 05.02.2024 Version number 4 Revision: 01.02.2024

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 30989-05-0 EINECS: 250-418-4 Reg.nr.: 01-2119462824-33- XXXX	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate Repr. 2, H361fd	<70%
CAS: 110-97-4 EINECS: 203-820-9 Reg.nr.: 01-21194754444-34- XXXX	1,1'-iminodipropan-2-ol Eye Irrit. 2, H319	<5%
	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol	<3%
	Eye Dam. 1, H318 Specific concentration limits: Eye Dam. 1; H318: C ≥ 30 % Eye Irrit. 2; H319: 20 % ≤ C < 30 %	

SVHC

Does not contain any or < 0,1% SVHC according to Regulation (EC) No 1907/2006 (REACH), Article 57.

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove contaminated clothes and shoes immediately.

After inhalation: Supply fresh air or oxygen; call for doctor.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

(Contd. on page 3)

(Contd. of page 2)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.02.2024 Version number 4 Revision: 01.02.2024

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. **Information about fire - and explosion protection:** No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Keep container tightly closed

Storage at room temperature.

Information about storage in one common storage facility:

Store away from flammable substances.

Store away from foodstuffs.

Further information about storage conditions: This product is hygroscopic.

Storage class according to TRGS 510: 10 combustible liquids.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Use skin protection cream for skin protection.

Respiratory protection:

If the occupational exposure limit is exceeded, a suitable respiratory protective device must be worn. Short term filter device:

Filter ABEK

Filter P3

(Contd. on page 4)

(Contd. of page 3)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.02.2024 Version number 4 Revision: 01.02.2024

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7 mm

NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Safety glasses

Body protection: Protective work clothing

Environmental exposure controls See section 6 and 7. No additional measures necessary.

Risk management measures

Ensure that activities are executed by specialists or authorised personnel only.

Use at industrial site in closed process with occasional controlled exposure or processes with equivalent containment conditions:

1 to 3 air changes per hour (90 % effectiveness) - basic standard of general ventilation maximum 8 h exposure duration per day

maximum 40 °C process temperature

Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

5 to 10 air changes per hour (90 % effectiveness) - good standard of controlled ventilation

maximum 1 h exposure duration per day

maximum 40 °C process temperature

Use of functional fluids in small devices:

5 to 10 air changes per hour (80 % effectiveness) - good standard of controlled ventilation

maximum 8 h exposure duration per day

maximum 40 °C process temperature

Use by private consumers.

Frequency of Exposure: ≤ 1 days per year

Supervision in place to check that the risk management measures installed are being used correctly and operation conditions followed.

Ensure control measures are regularly inspected and maintained.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid
Colour: Yellow
Odour: Characteristic
Odour threshold: Not determined.
Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range 270 °C (ASTM D 1120)

Flammability Not applicable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.

Flash point: 130 °C (DIN EN22719/ISO2719)

(closed cup)

Decomposition temperature: >450 °C (DSC) pH (50 g/l) at 20 °C 9 (ASTM D 1287)

(Contd. on page 5)



Printing date 05.02.2024 Version number 4 Revision: 01.02.2024

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

(Contd. of page 4)

Viscosity:

Kinematic viscosity at 20 °C 12.6 mm²/s (DIN 51562)

Dynamic: Not determined. water: Fully miscible.

Partition coefficient n-octanol/water (log

value) Not determined.

Vapour pressure at 20 °C: 0.27 Pa

Density and/or relative density

Density at 20 °C: 1.06 g/cm³ (DIN 51757)

Relative density

Vapour density

Not determined.

Not determined.

9.2 Other information No further relevant information available.

Appearance:

Form: Fluid

Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Void

Void

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard

classes **Explosives** Void Flammable gases Void Aerosols Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void **Pyrophoric solids** Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void Organic peroxides Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Corrosive to metals

Desensitised explosives

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide

(Contd. on page 6)



Printing date 05.02.2024 Version number 4 Revision: 01.02.2024

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

Nitrogen oxides (NOx)

(Contd. of page 5)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC5	0 valu	es relevant for classification:
30989-0	5-0 Tr	is[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate
Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
110-97-	4 1,1'-i	iminodipropan-2-ol
Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit)
Reactio	n mas	s of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rabbit)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Suspected of damaging fertility. Suspected of damaging the unborn child.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxic	city:	
EC50	>100 mg/l (bacteria) (OECD 209)	
LC50	>100 mg/L (fish) (DIN 38412 96 h)	
30989-05-0 T	ris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	
EC50	>100 mg/l (Algae) (72 h)	
	>100 mg/l (daphnia) (48 h)	
LC50	>100 mg/L (fish) (96 h)	
110-97-4 1,1'	-iminodipropan-2-ol	
EC50 (static)	EC50 (static) >100 mg/l (Algae) (72 h)	
	>100 mg/l (daphnia) (92/69/EWG 48 h)	
LC50 (static)	>100 mg/L (fish) (OECD 203 96 h)	
Reaction ma	ss of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol	
EC50	>100 mg/l (Algae)	
LC50	>100 mg/L (daphnia)	
	>100 mg/L (fish) (DIN 38412 96 h)	

12.2 Persistence and degradability No further relevant information available.

Other information: The product is easily biodegradable.

(Contd. on page 7)



Printing date 05.02.2024 Version number 4 Revision: 01.02.2024

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

(Contd. of page 6)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

	European	European waste catalogue 16 00 00 WASTES NOT OTHERWISE SPECIFIED IN THE LIST	
ľ	16 00 00		
	16 01 00	end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08)	
ľ	16 01 13*	brake fluids	

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number	
ADR, IMDG, IATA	Void
14.2 UN proper shipping name	
ADR, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordi	ing to
IMO instruments	Not applicable.
UN "Model Regulation":	Void

— IE



Printing date 05.02.2024 Version number 4 Revision: 01.02.2024

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

(Contd. of page 7)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients are listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients are listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients are listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients are listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients are listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients are listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H318 Causes serious eye damage.

H319 Causes serious eve irritation.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

Recommended restriction of use For industrial or professional purposes only.

Department issuing SDS:

Gefahrstoffmanagement Konzern ate.sicherheit@contiautomotive.com

Date of previous version: 01.07.2023

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

(Contd. on page 9)



Printing date 05.02.2024 Version number 4 Revision: 01.02.2024

Trade name: Original ATE Brake Fluid SUPER DOT 5.1

(Contd. of page 8)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Repr. 2: Reproductive toxicity – Category 2

http://echa.europa.eu/information-on-chemicals/cl-inventory

http://echa.europa.eu/web/guest/information-on-chemicals/registered-substances

http://www.reach-clp-biozid-helpdesk.de/de/Downloads/CLP-VO/CLP_VO_Anhang_VI_Tabelle_3_2.pdf http://www.safeworkaustralia.gov.au/

* Data compared to the previous version altered.