



Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 22.06.2023

Version number 5

Revision: 01.05.2023

1 Identification of the hazardous chemical and of the supplier

Product identifier

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

Article number: 03.9901-62xx.x / 7062xx

Recommended use of the chemical and restrictions on use

No further relevant information available.

Application of the substance / the mixture hydraulic liquid

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Continental Aftermarket & Services GmbH

Sodener Straße 9

D-65824 Schwalbach am Taunus

Tel: +49-6196-87-0

Further information obtainable from:

Gefahrstoffmanagement Konzern, Zentrales Materiallabor

ate.sicherheit@contiautomotive.com

Emergency telephone number:

Malaysia National Poison Centre, USM

National Poison Centre Universiti Sains Malaysia 11800 Penang Malaysia

Tel: +604-657 0099

Emergency number:

Office Hours: +604-657 0099 (Monday-Friday: 8.10am-5.10pm)

After Office Hours: +6012-430 9499 (including weekends and public holidays)

Fax: +604-656 8417

Email: prnnet@usm.my

2 Hazard identification

Classification of the substance or mixture



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Label elements

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms GHS08

Signal word Warning

Hazard-determining components of labelling:

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Hazard statements

H361 Suspected of damaging fertility or the unborn child.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

MY

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

(Contd. of page 1)

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate Repr. 2, H361	≥70-<90%
15520-05-5	2,2'-(Octylimino)bisethanol Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Aquatic Chronic 3, H412	≥3-<10%
111-46-6	2,2'-oxybisethanol Acute Tox. 4, H302	<5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

Description of first aid measures

General information: Remove contaminated clothes and shoes immediately.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Call a doctor immediately.

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

May be released in case of fire: CO, CO₂, NO_x

Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

MY

(Contd. on page 3)



Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 22.06.2023

Version number 5

Revision: 01.05.2023

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

(Contd. of page 2)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Storage at room temperature.

Information about storage in one common storage facility:

Store away from flammable substances.

Store away from foodstuffs.

Further information about storage conditions:

This product is hygroscopic.

Store in dry conditions.

Keep container tightly sealed.

Storage class according to TRGS 510: 10 combustible liquids.

Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see section 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Use skin protection cream for skin protection.

Respiratory protection:

Respiratory protection required in case of release of vapors / aerosols.

Use particulate filter with medium retention capacity for solid and liquid particles (eg EN 143 or 149, type P2 or FFP2).

(Contd. on page 4)

MY



Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 22.06.2023

Version number 5

Revision: 01.05.2023

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

(Contd. of page 3)

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7 mm

NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses

Body protection: Protective work clothing

Limitation and supervision of exposure into the environment

See section 6 and 7. No additional measures necessary.

9 Physical and chemical properties

Information on basic physical and chemical properties**General Information****Appearance:**

Form:	Fluid
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value at 20 °C: 7-8 ((50 %) FMVSS 116)

Change in condition

Melting point/freezing point	<-70 °C (DIN 51583)
Initial boiling point and boiling range	>280 °C (FMVSS 116)

Flash point: 141 °C (ASTM D 7094 (closed cup))

Flammability (solid, gas) Not applicable.

Auto-ignition temperature >200 °C (DIN 51794)

Decomposition temperature: ca. 360 °C (Analogy)

Auto-ignition temperature Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

Vapour pressure at 20 °C: <0.1 hPa

Density at 20 °C: 1.07-1.09 g/cm³ (DIN 51757)

Relative density Not determined.

Vapour density Not determined.

Evaporation rate Not determined.

water at 20 °C: 350 g/l

Partition coefficient: n-octanol/water Not determined.

Viscosity:

Dynamic: Not determined.

(Contd. on page 5)

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

(Contd. of page 4)

Kinematic at 20 °C:	17-18 mm ² /s
Solvent content:	
Organic solvents:	2.0 %
Other information	No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NO_x)

11 Toxicological information

Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:

30989-05-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
--------	------	-------------------------------

15520-05-5 2,2'-(Octylimino)bisethanol

Oral	LD50	1,157 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
--------	------	-------------------------------

111-46-6 2,2'-oxybisethanol

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)

Dermal	LD50	>5,000 mg/kg (rabbit)
--------	------	-----------------------

Primary irritant effect:

Skin corrosion or irritation Based on available data, the classification criteria are not met.

Serious eye damage or eye irritation

Based on available data, the classification criteria are not met.

Respiratory / skin sensitization Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (STOT) – single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) – repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

MY

(Contd. on page 6)



Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 22.06.2023

Version number 5

Revision: 01.05.2023

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

(Contd. of page 5)

12 Ecological information

Toxicity

Aquatic toxicity:

30989-05-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

EC50	>100 mg/l (Algae) (72 h)
	>100 mg/l (daphnia) (48 h)
LC50	>100 mg/L (fish) (96 h)

15520-05-5 2,2'-(Octylimino)bisethanol

EC50 (static)	1.35 mg/l (Algae) (OECD 201 72 h)
	>100 mg/l (bacteria) (OECD 209)
	19.1 mg/l (daphnia) (OECD 202 48 h)
LC50	22 mg/L (fish) (OECD 203 96 h)
ErC10 (static)	0.402 mg/L (Algae) (OECD 201 72 h)

111-46-6 2,2'-oxybisethanol

EC50	>100 mg/l (Algae)
	>100 mg/l (daphnia) (DIN 38412 T.11)
LC50	>100 mg/L (fish) (96 h)

Persistence and degradability No further relevant information available.

Other information: The product is easily biodegradable.

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment Not applicable.

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal information

Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14 Transportation information

UN-Number

ADR, ADN, IMDG, IATA

Void

(Contd. on page 7)

MY



Safety Data Sheet
according to P.U.(A) 310/2013

Printing date 22.06.2023

Version number 5

Revision: 01.05.2023

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

<http://www.safeworkaustralia.gov.au/>

*** Data compared to the previous version altered.**

(Contd. of page 7)

MY