

Safety Data Sheet according SS 586 : Part 3

Printing date 20.11.2025 Version number 7.0 Revision: 01.11.2025

1 Identification

Product identifier

Trade name: Original ATE Brake Fluid DOT 3 (blue)

Article number: 03.9901-03xx.x / 7003xx

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture hydraulic liquid

Details of the supplier of the safety data sheet

Manufacturer/Supplier: AUMOVIO Aftermarket GmbH

Cupriskostr 7

Guerickestr. 7

60488 Frankfurt a. M.

Germany

Tel: +49-69-76031

Importer: Name: Address:

Phone: e-Mail:

Further information obtainable from:

Hazardous Substances Management Aftermarket, Central Materials Laboratory ate.sicherheit@aumovio.com

Emergency telephone number:

INFOTRAC

- +1-352-323-3500 (International)
- +65 3163 5349 (National)

2 Hazards identification

Classification of the substance or mixture

The product is not classified, according to the Globally Harmonised System (GHS).

Label elements

GHS label elements Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Eye Dam. 1, H318

Specific concentration limits: Eye Dam. 1; H318: C ≥ 30 %

Eye Irrit. 2; H319: 20 % ≤ C < 30 %

(Contd. on page 2)

≥15-<20%



Safety Data Sheet according SS 586 : Part 3

Printing date 20.11.2025 Version number 7.0 Revision: 01.11.2025

Trade name: Original ATE Brake Fluid DOT 3 (blue)

143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	≥10-<15%
	Eye Dam. 1, H318	
	Specific concentration limits: Eye Dam. 1; H318: C ≥ 30 %	
	Eye Irrit. 2; H319: 20 % ≤ C < 30 %	
111-46-6	2,2'-oxybisethanol	≥5-<10%
	Acute Tox. 4, H302	
1559-34-8	3,6,9,12-Tetraoxahexadecan-1-ol	≥2.5-<5%
	Serious eye damage/irritation – Category 2A, H319	
	2-(2-methoxyethoxy)ethanol	≥2.5-<3%
	Repr. 1B, H360; Flammable liquids 4, H227 Specific concentration limit: Repr. 1B; H360D: C ≥ 3 %	
	Specific concentration limit: Repr. 1B; H360D: C ≥ 3 %	

Additional information:

For the wording of the listed hazard phrases refer to section 16.

CAS 143-22-6 and 1559-34-8 are part of the Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1ol, for which the SCL applies.

4 First-aid measures

Description of first aid measures

General information:

Remove contaminated clothes and shoes immediately.

Get medical advice/attention if you feel unwell.

After inhalation:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Seek medical treatment.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Call a doctor immediately.

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

May be released in case of fire: CO, CO2, NOx

Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

(Contd. of page 2)



Safety Data Sheet according SS 586 : Part 3

Printing date 20.11.2025 Version number 7.0 Revision: 01.11.2025

Trade name: Original ATE Brake Fluid DOT 3 (blue)

Ensure adequate ventilation

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about fire - and explosion protection: Temperature class: T3

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Storage at room temperature.

Information about storage in one common storage facility:

Store away from flammable substances.

Store away from foodstuffs.

Further information about storage conditions:

Store in dry conditions.

This product is hygroscopic.

Keep container tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Exposure controls

Additional information about design of technical facilities: No further data: see section 7.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Use skin protection cream for skin protection.

Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 4)

(Contd. of page 3)



Safety Data Sheet according SS 586 : Part 3

Printing date 20.11.2025 Version number 7.0 Revision: 01.11.2025

Trade name: Original ATE Brake Fluid DOT 3 (blue)

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7

mm

NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to

be observed.

Eye protection: Safety glasses

Limitation and supervision of exposure into the environment

See section 6 and 7. No additional measures necessary.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Colour: Blue

Odour: Characteristic
Odour threshold: Not determined.
pH-value at 20 °C: 7.5-10 (FMVSS 116)
Melting point/freezing point: <-70 °C (DIN 51583)

Initial boiling point and boiling range: >245 °C (FMVSS 116)

Flash point: ≥130 °C ((ASTM D 7094-closed cup)

Evaporation rateFlammability
Not determined.
Not applicable.

Explosion limits:

Lower: 1.5 Vol %

Upper: Not determined.

Vapour pressure at 20 °C: <10 hPa

Vapour pressure:

Vapour density Not determined.

Density at 20 °C: 1.04-1.07 g/cm³ (DIN 51757)

Relative density
water:

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

Decomposition temperature:

Not determined.

Not determined.

230 °C (DIN 51794)

>360 °C (DSC)

Viscosity:

Kinematic at 20 °C: 14.5-17 mm²/s (FMVSS 116)

Dynamic: Not determined.

Other information No further relevant information available.

Appearance:

Form: Fluid

Important information on protection of health

and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

10 Stability and reactivity

Reactivity No further relevant information available.

(Contd. on page 5)

(Contd. of page 4)



Safety Data Sheet according SS 586 : Part 3

Printing date 20.11.2025 Version number 7.0 Revision: 01.11.2025

Trade name: Original ATE Brake Fluid DOT 3 (blue)

Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

11 Toxicological information

Information on toxicological effects

Acute toxicity

LD/LC5	LD/LC50 values relevant for classification:					
Reactio	n mas	s of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol				
Oral	LD50	>5,000 mg/kg (rat)				
Dermal	LD50	>3,000 mg/kg (rabbit)				
111-46-	6 2,2'-0	oxybisethanol				
Oral	LD50	>5,000 mg/kg (rat)				
Dermal	LD50	>5,000 mg/kg (rabbit)				
111-77-	3 2-(2-	methoxyethoxy)ethanol				
Oral	LD50	>4,000 mg/kg (Guinea Pig) (OECD 401)				
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)				

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

Toxicity

Aquatic t	oxicity:
LC50	>100 mg/L (fish) (DIN38412)
Reaction	mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol
EC50	>100 mg/l (algae)
LC50	>100 mg/L (daphnia)
	>100 mg/L (fish) (DIN 38412 96 h)
111-46-6	2,2'-oxybisethanol
EC50	>100 mg/l (algae)
	>100 mg/l (daphnia) (DIN 38412 T.11)
	(Contd. on page

(Contd. on page 6)



Safety Data Sheet according SS 586: Part 3

Printing date 20.11.2025 Version number 7.0 Revision: 01.11.2025

Trade name: Original ATE Brake Fluid DOT 3 (blue)

(Contd. of page 5) >100 mg/L (fish) (96 h) LC50 111-77-3 2-(2-methoxyethoxy)ethanol EC50 (static) >100 mg/l (algae) (OECD 201 96 h) >100 mg/l (daphnia) (EPA 48 h) LC50 (static) >100 mg/L (fish) (EPA 96 h)

Persistence and degradability No further relevant information available.

Other information: The product is easily biodegradable.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable. Other adverse effects

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation Must be specially treated adhering to official regulations.

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

UN-Number		
ADR, IMDG, IATA	Void	
UN proper shipping name		
ADR, IMDG, IATA	Void	
Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
Packing group		
ADR, IMDG, IATA	Void	
Environmental hazards:	Not applicable.	
Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
Special precautions for user	Not applicable.	



Safety Data Sheet according SS 586 : Part 3

Printing date 20.11.2025 Version number 7.0 Revision: 01.11.2025

Trade name: Original ATE Brake Fluid DOT 3 (blue)

(Contd. of page 6)

UN "Model Regulation": Void

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act - Schedule 1

None of the ingredients are listed.

Poisons Act - Schedule 2, Group II

None of the ingredients are listed.

Health Products Act - First Schedule - Psychotropic Substances

None of the ingredients are listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

It is the sole responsibility of the importer or distributor to identify and comply with all legal requirements necessary for the lawful placing of chemical products on the market in the respective target countries.

Relevant phrases

H227 Combustible liquid.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

H360D May damage the unborn child.

Recommended restriction of use For industrial or professional purposes only.

Department issuing SDS:

Hazardous Substances Management Aftermarket

ate.sicherheit@aumovio.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flammable liquids 4: Flammable liquids - Category 4

Acute Tox. 4: Acute toxicity - Category 4

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Serious eye damage/irritation - Category 2A: Serious eye damage/eye irritation - Category 2A

Repr. 1B: Reproductive toxicity – Category 1B

* Data compared to the previous version altered.